



Wi-Fi CERTIFIED™ Interoperability Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing.
Learn more: www.wi-fi.org/certification/programs



Certification ID: WFA83725

Page 1 of 2

Date of Last Certification	August 29, 2019
Company	Ruckus Wireless, Inc.
Product	Ruckus R750
Model Number	Ruckus R750
Product Identifier(s)	
Category	Routers
Subcategory	Enterprise/Service Provider Access Point, Switch/Controller or Router
Hardware Version	Product: IPQ8074, Wi-Fi Component: IPQ8074
Firmware Version	Product: final_candidate_0802, Wi-Fi Component: final_candidate_0802
Operating System	Proprietary / Other: Embedded Linux
Frequency Band(s)	2.4 GHz, 5 GHz - Concurrent

Summary of Certifications

CLASSIFICATION	PROGRAM
Connectivity	Wi-Fi CERTIFIED 6™
	Wi-Fi CERTIFIED™ a, b, g, n, ac
	WPA™ – Enterprise, Personal
	WPA2™ – Enterprise, Personal
	WPA3™ – Enterprise, Personal
Optimization	Wi-Fi Enhanced Open™
	Wi-Fi Agile Multiband™
	WMM®



Security

WPA™ – Enterprise, Personal
WPA2™ – Enterprise, Personal
WPA3™ – Enterprise, Personal
EAP Type(s)
Any EAP Type
Protected Management Frames
192-bit Security

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

2.4 GHz, 5 GHz - Concurrent
3 Spatial Streams 2.4 GHz
3 Spatial Streams 5 GHz
Short Guard Interval
TX A-MPDU
STBC Transmit
40 MHz operation in 2.4 GHz, with coexistence mechanisms
40 MHz operation in 5 GHz

Wi-Fi CERTIFIED™ ac

4 Spatial Streams 5 GHz
Rx MCS 8-9 (256-QAM)
Tx STBC 2x1
Rx A-MPDU of A-MSDU
Tx SU beamformer
Low Density Parity Check coding
Tx DL MU-MIMO
RTS with BW Signaling
Extended 5 GHz Channel Support

Wi-Fi CERTIFIED 6™

4 Spatial Streams 2.4 GHz Rx
4 Spatial Streams 5 GHz Rx
Maximum Supported Channel Width (20, 40, 80 MHz)
DL MU-MIMO
SU Beamforming
DL OFDMA
UL OFDMA
Target Wake Time (TWT)
MCS 8-9 Rx
MCS 10-11 Rx
MU-BAR trigger frame
MU-RTS /CTS trigger frame
DL MU-PPDU with basic trigger frame

Wi-Fi CERTIFIED 6™ (continued)

Buffer Status Report (BSRP) trigger frame
256 Block Acknowledge (BA) Rx
256 Block Acknowledge (BA) Tx
MU EDCA Parameter set
Multiple-BSSID Set
Low Density Parity Check (LDPC) coding
Operating Mode Rx

Wi-Fi Enhanced Open™

ECC Group 20

Wi-Fi Agile Multiband™

Steer to Cellular Data
Fast Transition: WPA2-Enterprise and WPA2-Personal

WMM®

Spectrum and Regulatory Features

802.11d
802.11h