



35cm size w/ 60GHz + 5GHz



19cm size w/ 60GHz + 5GHz

MetroLinq™ 60

Cloud-Enabled Outdoor 60GHz PTP + 5GHz

IgniteNet™'s MetroLinq™ 60 is the world's first cost-effective 60GHz PTP/PTMP radio enabling high performance, interference-free connections worldwide. The MetroLinq™ 60 has an added advantage of being license-free in most markets globally, allowing ultra fast deployment and without the hassle of other frequency bands requiring a license. The MetroLinq™ 60 also includes a second 5GHz radio which can be configured as PTP (backup) to provide integrated redundancy without any additional hardware or complexity!

Interference-Free & Unlicensed Band

The IgniteNet™ MetroLinq™ 60 offers unprecedented performance - combining both the benefits of unlicensed band operation with no interference!

Dual Band 60GHz & 5GHz Operation

The MetroLinq™ 60 includes a second 5GHz radio which can be configured as a backup to the 60GHz to provide automatic failover during adverse conditions. This allows links to be extended further without effecting link availability.

Powerful, Flexible Configuration

The MetroLinq™ 60 can operate either as a stand-alone device or as a coordinated, cloud-managed device, easily meeting the requirements of any installation.

Robust Weather-Resistant Design

The MetroLinq™ 60 features a hybrid metal/plastic design built to withstand the harshest environments including precipitation, hot/cold weather and high/low humidities.

PRODUCT VARIANTS

- > 35cm size w/ 60GHz + 5GHz
- > 19cm size w/ 60GHz + 5GHz

FEATURES

HARDWARE FEATURES

- > 2x Gigabit Ethernet Port (PoE IN)
- > 1x Power tap (Power OUT)
- > 1x USB 2.0 Port (optional)
- > Dual flash image support

LEDs

- > Power, Ethernet, Wireless, Health/Status, Aiming

DIMENSIONS (L x W x H)

- > 350 x 350 x 200 mm/ 13.78 x 13.78 x 7.87 inch (ML-60-35)
- > 190 x 190 x 120 mm/ 7.48 x 7.48 x 4.72 inch (ML-60-19)

WEIGHT

- > 3.5 kg/ 7.72 lb with mount (ML-60-35)
- > 2 kg/ 4.41 lb with mount (ML-60-19)

POWER

- > **24V/1A passive Gigabit PoE**
- > 15W max power consumption

OPERATING ENVIRONMENT

- > Operating Temperature: -30 to +55 C°/ -22 to 131 F
- > Store Temperature: -30C° to 55C°
- > Operating Humidity: 10 to 90% non-condensing (RH)

REGULATORY / STANDARDS COMPLIANCE

- > FCC/IC
- > CE

RANGE

- > Up to 1.5 km/ 0.93 mi (ML-60-35, location dependent)
- > up to 0.9 km/ 0.58 mi (ML-60-19, location dependent)

RF PERFORMANCE (TX)

- > 60GHz: 14dBm @ 2.5Gbps OTA (1Gbps aggregate throughput)
- > 5GHz: 24dBm @ 866Mbps OTA (500Mbps aggregate throughput)

RF PERFORMANCE (RX)

- > 60GHz: -74dBm @ MCS1; -65 @ MCS5; -60dBm @ MCS9
- > 5GHz: -94dBm @ MCS0; -64dBm @ MCS15

CHANNEL BANDWIDTH

- > 60GHz: 2GHz
- > 5GHz: 80MHz, 40MHz, 20MHz

KEY FEATURES

- > 1Gbps Aggregate throughput; dynamically allocated (60GHz)
- > 500Mbps Aggregate throughput; dynamically allocated (5GHz)
- > Jumbo packet support (up to 7900bytes)
- > Management VLAN support and VLAN pass-through
- > Supports Service Provider and Enterprise type networks
- > **Stand-alone** or Cloud-controlled operating modes
- > PTP/Client modes with Flexible Bridging (60GHz)
- > Link failover/backup (60GHz + 5GHz PTP Mode)
- > 128bit AES Encryption (standard; 5GHz and 60GHz)

APPLICATIONS

- > Fixed Wireless Access (broadband)
- > 3G/4G Backhaul
- > Metro WiFi
- > Campus Interconnection
- > Hybrid Fiber/Wireless Networks

ORDERING INFORMATION

Part Number	Description
ML-60-35-XX	60GHz Outdoor PTP + 5GHz w/ Integrated 42dBi (60GHz) and 22dBi (5GHz) antenna
ML-60-35-1-XX	60GHz Outdoor PTP + 5GHz w/ Integrated 42dBi (60GHz) and RPSMA Connectors (5GHz)
ML-60-19-XX	60GHz Outdoor PTP + 5GHz w/ Integrated 36dBi (60GHz) and 16dBi (5GHz) antenna
ML-60-19-1-XX	60GHz Outdoor PTP + 5GHz w/ Integrated 36dBi (60GHz) and RPSMA Connectors (5GHz)

****XX IS USED TO DENOTE LOCALIZATION (US, EU, AU, CN)**



Worldwide
20 Mason
Irvine, CA 92618
USA
sales@ignitenet.com

Distributor Eestis
3kgroup OÜ
Pärnu mnt 139c Tallinn
tom@3kgroup.ee
55514009

